Telephone:

1. Identification

Name of the product: **Optik-Wipes**

Product Identification Number(s): 2067

Recommended use: Surface wipe. Use not recommended: Body wipe.

Company: Control Company

12554 Old Galveston Rd, Suite B230 Webster, TX 77598

Product Information: 800-342-3577

Fax number: 580-327-3579 CHEMTREC (Transportation): 1-800-424-9300

800-342-3577

SDS Code: CC OW1

Date prepared: March 12, 2015

CPR STATEMENT: This product has been classified in accordance with the hazard criteria of the Canadian Controlled Products Regulations (CPR) and the SDS contains all the information required by the CPR.

2. Hazard(s) identification

Emergency Overview

OSHA Hazards

Flammable liquid, Target Organ Effect, Irritant

Other hazards which do not result in classification are: May form explosive peroxides.

GHS Classification

Flammable liquids (Cat. 2)

H225 Highly flammable liquid and vapor.

Skin irritation (Cat. 3)H316 Causes mild skin irritation.Serious eye damage (Cat.1)H318 Causes serious eye damage.

Specific target organ toxicity - single exposure (Cat. 3)

GHS Label elements, including precautionary statements

Pictogram:



Signal word:

Hazard statements:

H225 Highly flammable liquid and vapor.

H316 Causes mild skin irritation.

H318 Causes serious eye damage.

H336 May cause drowsiness or dizziness.

Precautionary statements:

P210 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

P261 Avoid breathing dust/ fume/ gas/ mist/ spray.

P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

3. Composition / Information on ingredients

Chemical identity:	1-Propanol	100%
Common name:	n-Propanol	
Numbers of identity:	CAS. 71-23-8	EC 200-746-9
Impurities: None of toxicological significance.		

4. First-aid measures

P304+313 +341 IF INHALED: If breathing is difficult, remove victim to fresh air and keep at rest in a position comfortable for breathing. Consult a physician.

P302+352 IF ON SKIN: Wash with soap and water.

P305+351+338 IF IN EYES: Rinse continuously with water for several minutes.

Remove contact lenses if present and easy to do; continue rinsing.

P301+330+331 IF SWALLOWED: Rinse mouth. Do NOT induce vomiting.

Most important symptoms and effects, both acute and delayed: Severe eye irritation. Skin irritation.

5. Firefighting measures

Suitable extinguishing equipment:

Water spray, alcohol-resistant foam, dry chemical or carbon dioxide.

Emergency procedures:

Eliminate ignition source. Evacuate unnecessary personnel. Call appropriate fire fighting crew.

Special protective equipment for firefighters

Wear self contained breathing apparatus for fire fighting if necessary.

Hazardous decomposition products formed under fire conditions. - Carbon oxides, product vapors.

Use water spray to cool unopened containers.

6. Accidental release measures

Use personal protective equipment. Avoid breathing, mist or vapors. Ensure adequate ventilation. Remove all sources of ignition. Evacuate personnel to safe areas. Be aware of possible accumulating vapors which could form explosive concentrations. Vapors can accumulate in low areas. Environmental precautions:

Prevent further leakage or spillage if safe to do so. Do not let product enter drains.

Methods and materials for containment and cleaning up

Contain spillage, and then absorb with industrial absorbent, or collect with an electrically protected vacuum cleaner or by wet-brushing and place in container for disposal according to local regulations. See also Sec. 13.

7. Handling and storage

Precautions for safe handling:

Avoid contact with skin and eyes. Avoid inhalation of vapors or mist.

Use explosion-proof equipment. Keep away from sources of ignition - No smoking.

Prevent the build up of electrostatic charge.

Conditions for safe storage:

Keep container tightly closed in a dry and well-ventilated place.

Containers which have been opened must be resealed and kept upright to prevent leakage.

8. Exposure controls / personal protection

Information on the system design:

Product is intended for external use only. Stay up wind, out of any spray developed.

Exposure Limits:		Reference 29Cl	FR 1910.1000 Table Z-1
Component Name, CAS#		OSHA PEL	ACGIH TLV
1-Propanol 71-23-8		200 ppm	100 ppm
Personal protective equipn	nent :		
Respiratory protection:	Where appropriate use a ful	I-face supplied air	respirator.
Hand protection:	Rubber gloves.		
Eye protection:	Safety glasses with side-shi	elds.	
Skin and body protection:	Chemical resistant apron or	protective suit if s	plashing or repeated contact
with solution	on is likely; flame retardant and	l antistatic propert	ies are recommended.
Hygiono moscuros : Hong	lla in accordance with good in	ductrial bygiona a	nd cofoty practico

Hygiene measures : Handle in accordance with good industrial hygiene and safety practice. Wash hands and face before breaks and immediately after handling the product.

9. Physical and chemical properties

•••••			
Appearance:	Clear, colorless liquid		
Odor:	Alcoholic		
Odor threshold:	No data available		
pH-value:	Not applicable		
Melting/ freezing point:	127 °C (-197 °F) - literature		
Initial boiling point:	97 °C (207 °F)		
Flash point:	22 °C (72 °F) - closed cup		
Evaporation rate:	ation rate: no data available		
Flammability (solid, gas): Not applicable			
Explosion limits: Lower: 2.1 V% Upper: 13.7V% (Isopropyl alcohol)			
Vapor pressure:	19.3 hPa (14.5 mmHg) at 20 °C (68 °F)		
Vapor density:	2.07 (Air = 1)	Auto-ignition temperature:	400 °C (752 °F)
Relative density (water	Decomposition temperature	: No data	
Solubility: Totally solub	Solubility: Totally soluble in water at 20°C Viscosity: Like water		
Partition coefficient: Log Kow: log Pow: 0.25 - 0.34 octanol/water			

10. Stability and reactivity

Chemical stability: No decomposition, if used according to specifications.
Possibility of hazardous reactions: May form explosive mixture with air.
Conditions to avoid: Heat, flames and sparks. Extremes of temperature and direct sunlight.
Materials to avoid: Oxidizing agents
Hazardous decomposition products: Carbon oxides, product vapors.

11. Toxicological information

· · · · · · · · · · · · · · · · · · ·		
There is no data available for the pr	oduct.	
Routes of Entry: Absorbed through	n skin. Eye contact. Inhalation.	
Oral Toxicity LD 50:	Rat 8,038 mg/kg	
Dermal Toxicity LD 50:	Rabbit 4,000 mg/kg	
Inhalation Toxicity, LC50:	Rat 20000 ppm, 1 hr	
Eye Irritation (Rabbit)	Severe irritation	
Dermal Irritation (Rabbit)	No irritation	
Chronic Effects on Humans:		
No component >0.1% listed by NTF	P, IARC, OSHA or ACGIH as a suspect or potential carcinogen.	
California Prop. 65 chemicals: This	product does not contain any chemicals known to State of	
California to	cause cancer, birth defects, or any other reproductive harm.	
Contains material which may cause damage to the following organs: kidneys, liver, CNS,		
Signs and Symptoms of Exposure	Central nervous system depression, prolonged or repeated exposure	

Signs and Symptoms of Exposure: Central nervous system depression, prolonged or repeated exposure can cause:, nausea, dizziness, narcosis or drowsiness.

12. Ecological information

Ecotoxicity: 1-Propanol

Toxicity to fish: LC50 - Pimephales promelas (fathead minnow) - 4,555 mg/l - 96 h

Toxicity to daphnia and EC50 - Daphnia magna (Water flea) - 3,642 mg/l - 48 h

Products of Biodegradation:

The product is miscible in water and readily biodegradable in both water and soil. Accumulation is not expected. Mobility in soil No data available

Optik-Wipes

Page 4 of 4

Results of PBT and vPvB assessment

PBT/vPvB assessment not available No data available.

13. Disposal considerations

Product as made has the characteristic of ignitability, like "Unlisted Hazardous Waste D001", RQ 100#. Burn in a chemical incinerator equipped with an afterburner and scrubber. Dispose in accordance with local, state and federal regulations.

14. Transport information

Reportable Quantity (RQ):

DOT (US)

UN1274 n-Propanol, Class 3, PG II

Not possible in one non bulk packabe

Marine pollutant: No May also be shipped Consumer Commodity ORM-D

The description shown may not apply to all shipping situations. Consult 49CFR, OSHA or appropriate Dangerous Goods Regulations, for additional description requirements (e.g., technical name, labeling) and mode-specific or quantity-specific shipping requirements,

15. Regulatory information

OSHA Hazards: Hazard Communication Standard (29 CFR 1910.1200).

Flammable liquid, Target Organ Effect, Irritant

SARA 302 Components: None

SARA 313 Components: None

Inventory Status: All components are on TSCA, EINECS/ELINCS, AICS, and DSL.

Federal and State Regulations:

State Right to Know lists (RTK):

n-Propanol

MA, PA, NJ

OSHA: Hazardous by definition of Hazard Communication Standard (29 CFR 1910.1200).

Flammable liquid, Target Organ Effect, Irritant

WHMIS (Canada): CLASS B-2: Flammable liquid with a flash point lower than 37.8°C (100°F). CLASS D-2B: Material causing other toxic effects: None

California Prop. 65 Components: This product does not contain any chemicals known to State of California to cause cancer, birth defects, or any other reproductive harm.

SDS Preparation date:	Marcl	n 12, 2015			
Hazard Categories:	Health	Fire	Pressure	Reactivity	Reference 49 CFR 171.8,
Immediate	Yes	Yes	No	No	OSHA 29 CFR 1910.1200 and
Delayed	Yes	No	XXX	XXX	SARA 302/311/312/313.
HMIS Hazard ratings: Health 2 Fire 3 Instability 0 Other B (Goggles, gloves)					
Hazard Ratings: Least: 0 Slight: 1 Moderate: 2 High: 3 Extreme: 4				eme: 4	

HMIS® is a registered trade and service mark of the NPCA.

Note: The information in this SDS was obtained from current reputable and competent sources.

However, the data is provided without warranty, expressed or implied, regarding its correctness or accuracy. It is the user's responsibility to determine safe conditions for the use of this product and to assume liability for loss, injury, damage or expense resulting from improper use of this product.

This SDS is designed for workplace employees, emergency personnel and for other conditions and situations where there is a greater potential for large-scale or prolonged exposure, in accordance with requirements of the U.S. Government's Occupational Safety and Health Administration (OSHA).