

Traceable® Thermometer/Clock/Humidity Monitor

Simultaneously displays time of day, temperature, and humidity



Monitor with memory your lab environment

- Features: Min/Max memory, memory clear, °F/°C switchable, 12/24-hour clock
- At the touch of a button, memory recalls the highest and lowest temperature and humidity readings
- Internal sensors make it ideal for use in hoods, storerooms, cleanrooms, incubators, drying chambers and environmental cabinets

Features:

- Min/Max memory for temperature and RH
- Simple memory recall and clear
- Individually serialized, calibrated, and certified Traceable® to NIST

Displays:

- Ambient Relative Humidity
- Ambient Temperature
- Time



Convenient unit sits on bench, hung on the wall, or may be placed anywhere

Traceable to NIST for accuracy

An individually-numbered Traceable® Certificate is provided which assures accuracy from an ISO/IEC 17025 (1750.01) calibration laboratory accredited by A2LA. It indicates traceability to standards provided by NIST (National Institute of Standards and Technology).

Cat. No. 4040 Traceable® Thermometer/Clock/Humidity Monitor

Product Specifications

- ▶ **Humidity**
 - Range:** 20 to 90% RH
 - Resolution:** 1% RH
 - Accuracy:** ±5% RH mid-range to ±8% RH elsewhere
- ▶ **Ambient Temperature**
 - Range:** 32.0 to 122.0°F (0.0 to 50.0°C)
 - Resolution:** 0.1°
 - Accuracy:** ±1°C
- ▶ **Timing**
 - Capacity:** 12/24 hours
 - Resolution:** 1 minute
 - Accuracy:** 0.01%
- ▶ **Supplied:** Traceable® Certificate, flip-open stand, wall mount, double-back tape, and batteries

