

# Traceable® Platinum High-Accuracy Freezer Thermometers

**Extreme accuracy—  
Platinum wide-range**




Cat. No. 6411

## View the time and date MIN/MAX readings occurred

- Triple display shows current, MIN/MAX temperatures
- Time/date stamp key shows exact time and date for all MIN/MAX readings
- Smart-Alarm™—a visual/audible alarm that continues to alarm even if unit returns to non-alarm conditions

## Features:

- Unique history program displays MIN/MAX temperatures for previous 24 hours (for each hour); and previous 7-days (for each day) or previous 31 days (for each day)
- °C/°F switchable
- Sealed GRAS bottle is insulated from rapid temperature changes when door is opened; GRAS—liquid generally recognized as safe by US Food and Drug Administration
- Alarm is settable in 0.1° increments and signals when temperature rises above/ falls below set points



6408

6409/6411

6410

## Traceable to NIST for accuracy

An individually-numbered Traceable® Certificate is provided which assures accuracy from an ISO/IEC 17025:2005 (1750.01) calibration laboratory accredited by A2LA. It indicates traceability to standards provided by NIST (National Institute of Standards and Technology).

- Cat. No. 6408 Traceable® Platinum High Accuracy Thermometer, 1 Bottle Probe
- Cat. No. 6409 Traceable® Platinum High Accuracy Thermometer, 1 Bullet™ Probe
- Cat. No. 6410 Traceable® Platinum High Accuracy Thermometer, 1 SS Probe
- Cat. No. 6411 Traceable® Platinum High Accuracy Thermometer, 1 Bullet™ Probe

## Product Specifications

- ▶ **6408/6409**  
Range: -58.00 to 158.00°F (-50.00 to 70.00°C)
- ▶ **6410**  
Range: -148.00 to 199.99°F (-100.00 to 199.99°C)
- ▶ **6411**  
Range: -148.00 to 158.00°F (-100.00 to 70.00°C)
- ▶ **Resolution:** 0.01°
- ▶ **Accuracy:** ±0.1°C
- ▶ **Size:** 2¼ x 4¼ x ¾"
- ▶ **Weight:** 5 ounces
- ▶ **Supplied:** batteries, probe, cable, magnetic strips, hook and loops tape, bench stand, Traceable® Certificate